



# RASICK VIS

## SAE 15W-40

RASICK Vis 15W-40 is a multi-grade lubricant that maintains the lubrication film at extreme temperatures. Formulated for high-performance, high-power engines that navigate roads and/or cities in harsher conditions.

### APPLICATIONS

In modern diesel engines requiring using high or low sulfur fuel. This includes heavy-duty trucks and buses. It is also applied in mining and construction and agricultural equipment.

### FEATURES

- Good thermal stability and resistance to oxidation, allowing an adequate life of the oil.
- Good protection against engine wear.
- Good control of oil consumption.
- Control of piston deposits, compared to previous API performance categories.
- Good engine performance in extreme conditions with high and low sulfur fuel.

### SPECIFICATIONS

Meets and exceeds the Service categories:  
- API CF-4

Meets the requirements of OEM manufacturers:

- MB 228.1
- MAN 270

### HEALTH & SAFETY

This product does not pose a risk to health or safety as long as they maintain good personal and industrial hygiene practices. In case of contact with skin, wash immediately with soap and water. Do not throw used oil into drains or drains. Dispose of waste responsibly. For more information, ask for the Safety Data Sheet.

### PRESENTATION

#### RASICK VIS 15W-40

Bottle ¼ gal  
2.5 gal pail  
3.785 L gallon  
4 gal pail  
5 gal Drum

### TYPICAL CHARACTERISTICS

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES
SAE Grade		SAE J300	15W-40
API Service		SAE J183	CH-4
Kinematic viscosity @ 40°C	cSt	ASTM D-445	
Kinematic viscosity @ 100°C	cSt	ASTM D-445	
Viscosity Index		ASTM D-2270	
Flash Point	°C	ASTM D-92	
Max Pour Point	°C	ASTM D-97	
Relative density @15°C	Kg/L	ASTM D-4052	
Total Basic Number, TBN	mgKOH/g	ASTM D-2896	

In manufactured batches, there may be slight variations in the average values, which do not affect the quality or performance of the product.