



RAYVON ATTOM 4T 20W-40

Rayvon Attom 4T is a high-performance full synthetic oil lubricant developed with Polyfriction Technology (PFM) that reduces friction under extreme operating conditions in both clutch, gear and transmission systems. Its lower degree of viscosity helps the engine work at a higher level of efficiency.

APPLICATIONS

Recommended for 4-stroke engines in motorcycles, motocross, enduro, scooters, choppers and ATVs of all types of brands.

FEATURES

- Adequate friction properties leading to better clutch operation.
- Excellent cleaning of the engine and pistons.
- Easy cold start, good fluidity at low temperatures.
- Oxidation control at high temperatures that minimizes deposits.
- Prolongs engine life due to excellent wear protection (EP)
- It extends the change periods due to its lower oil consumption.

SPECIFICATIONS

Meets the service level:

- API SN, JASO MA2

HEALTH & SAFETY

This product does not pose a risk to health or safety as long as they maintain good personal and industrial hygiene practices. In case of contact with skin, wash immediately with soap and water.

Wear gloves when handling used oils. Do not dispose of the waste down the sewer. Take care of our environment.

PRESENTATION

RAYVON ATTOM 4T 20W-40

1 L bottle
3.785 L gallon

TYPICAL CHARACTERISTICS

PHYSICOCHEMICAL TEST	UNIT	METHOD	AVERAGE VALUES
SAE Grade		SAE J 300	20W-40
Density @ 15°C	Kg/L	ASTM D-4052	
Kinematic viscosity @ 40°C	cSt	ASTM D-445	
Kinematic viscosity @ 100°C	cSt	ASTM D-445	
Viscosity Index		ASTM D-2270	
Total Base Number	mg KOH/g	ASTM D-2896	
Flash Point	°C	ASTM D-92	
Pour Point	°C	ASTM D-97	

In manufactured batches, there may be slight variations in the average values, which do not affect the quality or performance of the product.