



## TRAKAGRA MO

### SAE 20W-40

High viscosity multigrade oil, formulated for diesel engines that work in severe conditions. Its technology provides high protection power for the internal parts of the engine.

#### APPLICATIONS

Trakagra MO SAE 20W-40 is designed to be applied to tractor engines in harsh working conditions.

Recommended for applications where the manufacturer specifies an API CF-4 motor oil category.

#### FEATURES

- Good thermal stability and resistance to oxidation, allowing an adequate life of the oil.
- Good protection against engine wear.
- Good engine performance in extreme conditions with high and low sulfur fuel.

#### SPECIFICATIONS

Meets service level:  
- API CF-4

#### HEALTH & SAFETY

This product does not pose a risk to health or safety as long as they maintain good personal and industrial hygiene practices. In case of contact with skin, wash immediately with soap and water.

Wear gloves when handling used oils. Do not dispose of the waste down the sewer. Take care of our environment.

#### TYPICAL CHARACTERISTICS

PHYSICOCHEMICAL TEST	UNIT	METHOD	AVERAGE VALUES
SAE Grade		SAE J 300	20W-40
Density @ 15°C	Kg/L	ASTM D-4052	
Kinematic viscosity @ 40°C	cSt	ASTM D-445	
Kinematic viscosity @ 100°C	cSt	ASTM D-445	
Viscosity Index		ASTM D-2270	
Total Base Number	mg KOH/g	ASTM D-2896	
Apparent viscosity, C.C.S @ -10°C	cP	ASTM D-5293	
Flash Point	°C	ASTM D-92	
Pour Point	°C	ASTM D-97	

In manufactured batches, there may be slight variations in the average values, which do not affect the quality or performance of the product.

#### PRESENTATIONS

TRAKAGRA MO SAE 20W-40
5 gal pail
55 gal drum
3.785 L Gallon
1L Bottle