

Rayvon Attom 4T 15W-50

Rayvon Attom 4T 15W-50 is a premium engine oil designed for 4-Stroke 2-wheeler engines. This oil is formulated with Fully Synthetic base stock and Listoil's unique Hi-Pro Friction technology that provides superior protection for engine, clutch and gears. It is designed to perform in modern 4-Stroke 2-wheeler engines in wide temperature and riding range. This advance additive technology provides smooth riding experience, good pick-up and optimum clutch performance. Rayvon Attom 4T 15W-50 helps in extending engine life even in the extreme conditions. It is developed for high CC bikes and riders who loves to ride with 2-wheelers.

FEATURES & BENEFIT

- Adequate friction properties leading to better clutch operation.
- Excellent cleaning of the pistons and other critical engine parts.
- Easy cold start, good fluidity at low temperatures.
- Oxidation control at high temperatures that minimizes deposits.
- Prolongs engine life due to excellent wear protection.
- It extends the change periods due to its lower oil consumption.

APPLICATIONS

Suitable for all modern 4-stroke high CC 2-wheeler engines for wide range of application where API SN or backward API grades and JASO MA-2 specifications are recommended by OEMs. Recommended for 4-stroke engines equipped with catalytic converters to reduce emissions. It can provide adequate level of protection for the engine transmission and clutch, particularly in high performance engines, that tend to operate at higher temperatures and high RPM.

SPECIFICATIONS for 15W-50

Meets the following specifications:

- API SN
- JASO MA-2

Typical Characteristics

Test Parameter	Units	Test Methods	15W-50
Appearance		Visual	Clear & Bright
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	133.4
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	18.36
Viscosity Index		ASTM D-2270	154
Flash Point	°C	ASTM D- 92	-24
Pour Point	°C	ASTM D-97	236
Relative density @15°C	Kg/L	ASTM D-4052	0.8597
Total Base Number, TBN	mg KOH/g	ASTM D -2896	7.9

In manufactured batches, there may be slight variations in the average values, which do not affect the quality or performance of the product.

The test results listed above & within the report relate only to the specific samples checked/tested on the dates indicated. These reports/specifications must not be reproduced, partial/full, and can't be used for any legal purpose without the written approval from Vistony India Pvt. Ltd. Barrels/small packs should be stored preferably indoor. It should not be stored above 60°C, avoid exposure to Sun or freezing conditions. Do not discharge in drains, soil, or water. Take used oil to an authorized collection point only. above 60°C, avoid exposure to sun or freezing conditions. Do not discharge in drains, soil, or water. Take used oil to an authorized collection point.