

Rayvon Sytkoil 4T 20W-40

Rayvon Sytkoil 4T 20W-40 is a superior quality engine oil designed for 4-Stroke 2-wheeler engines. Formulated with specially chosen premium base stocks and Hi-Pro Friction technology that provides improved protection for engine, clutch and gears. It is designed to perform in modern 4-Stroke 2-wheeler engines in wide temperature and riding range. It is designed to provide better sludge control and shear stability for a smooth riding, good pick up and longer component life. This will provide good thermal stability, wear protection during extreme conditions. It is suitable for all modern motorcycle engines where API SN or backward grades are mentioned, and JASO MA-2 specifications are recommended.

FEATURES & BENEFIT

- Synthetic technology (to validate) oil with provides good performance in engine protection.
- Adequate friction properties leading to better clutch operation.
- Excellent cleaning of the engine and pistons.
- Easy cold start, good fluidity at low temperatures.
- Oxidation control at high temperatures, minimized deposits.
- Prolongs engine life due to excellent wear protection
- Extended change periods due to lower oil consumption.

APPLICATIONS

Suitable for all modern 4-stroke 2-wheeler engines for wide range of applications where API SN or backward API grades service categories and JASO MA-2 specifications are recommended by OEMs. It can provide adequate level of protection for the engine transmission and clutch, particularly in air-cooled engines, which tend to operate at higher temperatures.

SPECIFICATIONS for 20W-40

Meets the following specifications:

- API SN
- JASO MA-2

Typical Characteristics

Test Parameter	Units	Test Methods	Average Values
SAE Grade		SAE J300	20W-40
Appearance		Visual	Clear & Bright
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	113
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	14.7
Viscosity Index		ASTM D-2270	134
Flash Point	°C	ASTM D- 92	-33
Pour Point	°C	ASTM D-97	238
Relative density @15°C	Kg/L	ASTM D-4052	0.8667
Total Base Number, TBN	mg KOH/g	ASTM D -2896	7.7

In manufactured batches, there may be slight variations in the average values, which do not affect the quality or performance of the product.

The test results listed above & within the report relate only to the specific samples checked/tested on the dates indicated. These reports/specifications must not be reproduced, partial/full, and can't be used for any legal purpose without the written approval from Vistony India Pvt. Ltd. Barrels/small packs should be stored preferably indoor. It should not be

stored above 60°C, avoid exposure to Sun or freezing conditions. Do not discharge in drains, soil, or water. Take used oil to an authorized collection point only.